



# HALO 3 CH<sub>4</sub>

## Trace Level Methane Analyzer

GASES & CHEMICALS

CEMS

ENERGY

ATMOSPHERIC

SEMI & HB LED

SYNGAS

LAB & LIFE SCIENCE

### Designed for trace level methane analysis, the HALO 3 CH<sub>4</sub> offers:

- Low single-digit parts per billion (ppb) methane detection capability in an array of gases
- Absolute measurement (freedom from calibration gases)
- Wide dynamic range
- Low cost of ownership and operational simplicity
- Clean technology—no external calibration gases required
- Compact analyzer footprint

The HALO 3 CH<sub>4</sub> trace level methane gas analyzer provides users with the unmatched accuracy, reliability, speed of response and ease of operation that users of Tiger Optics analyzers have come to know and expect. Featuring Tiger Optics' proven Cavity Ring-Down Spectroscopy-based trace gas sensor in a very compact and economic analyzer design, this versatile analyzer allows users to measure methane in most inert and passive gases with just one device.

Users also enjoy freedom from requirements such as periodic sensor maintenance, span calibrations, purifier replacement and pump rebuilds. As a result, the HALO is ideally suited to many applications where trace gas measurement is extremely critical. These applications include silicon wafer manufacturing monitoring, fixed bulk gas continuous quality control, process tool monitoring, air separation, gas cylinder quality control and many other demanding applications.

**Tiger**optics

21<sup>ST</sup> CENTURY SPECTROSCOPY

# HALO 3 CH<sub>4</sub>

## Trace Level Methane Analyzer



Performance	
Operating range	See table below
Detection limit (LDL, 3σ/24h)	See table below
Precision (1σ, greater of)	± 0.75% or 1/3 of LDL
Accuracy (greater of)	± 4% or LDL
Speed of response	< 1 minute to 95%
Environmental conditions	10°C to 40°C 30% to 80% RH (non-condensing)
Storage temperature	-10°C to 50°C

Gas Handling System and Conditions	
Wetted materials	316L stainless steel (corrosive gas version optional) 10 Ra surface finish
Gas connections	1/4" male VCR inlet and outlet
Leak tested to	1 x 10 <sup>-9</sup> mbar l / sec
Inlet pressure	30 – 125 psig (3.1 – 9.6 bara)
Flow rate	Up to 1.8 slpm
Sample gases	Most inert, toxic, passive and corrosive matrices
Gas temperature	Up to 60°C

Dimensions	H x W x D [in (mm)]
Standard sensor	8.73 x 8.57 x 23.6 (222 x 218 x 599)
Sensor rack (fits up to two sensors)	8.73 x 19.0 x 23.6 (222 x 483 x 599)

Weight	
Standard sensor	28 lbs (12.7 kg)

Electrical	
Alarm indicators	2 user programmable 1 system fault Form C relays
Power requirements	90 – 240 VAC, 50/60 Hz
Power consumption	40 Watts max.
Signal output	Isolated 4–20 mA per sensor
User interfaces	5.7" LCD touchscreen 10/100 Base-T Ethernet 802.11g Wireless (optional) RS-232 Modbus TCP (optional)
Certification	CE Mark

Performance, CH <sub>4</sub> :	Range	LDL (3σ)	Precision (1σ) @ zero
In Nitrogen	0 – 8 ppm	1.6 ppb	0.6 ppb
In Helium	0 – 5 ppm	1.1 ppb	0.4 ppb
In Argon	0 – 7 ppm	1.4 ppb	0.5 ppb
In Hydrogen	0 – 8 ppm	1.6 ppb	0.6 ppb
In Oxygen	0 – 6 ppm	1.1 ppb	0.4 ppb

Contact us for additional analytes and matrices.  
U.S. Patent # 7,277,177

**Tiger Optics, LLC**  
250 Titus Avenue, Warrington, PA 18976  
Phone: +1 (215) 343 6600 • Fax: +1 (215) 343 4194  
sales@tigeroptics.com • www.tigeroptics.com